

IMPAC® Premium PRO

10 YEAR WHITE ELASTOMERIC ROOF COATING

Description:

IMPAC® Premium PRO is an acrylic resin based elastomeric roof coating. Highly reflective, environmental friendly, common structural movement resistant, prevents moisture filtrations and leaks.

Benefits:

- IMPAC® Premium PRO is easy to apply. Now with better adherence, it has the exclusive UV-SHIELD II sun block which provides properties to preserve the whiteness and elasticity of the roof coating.
- Environmental friendly, formulated in an aqueous base without solvents nor harmful components
- This product can give points for LEED Certification

Uses:

- IMPAC® Premium PRO adheres to the most common construction materials, such as concrete, galvanized sheet metal, fibrocement boards, bricks, wood, and ducts.
- Apply with a paintbrush or brush on any type of construction such as: institutional buildings and housing, warehouses, industrial facilities, commercial buildings and homes
- Consider perimetral banding on critical points or areas with IMPAC® Super Reinforcement Fabric.

Recommendations:

Do not apply at temperatures lower than 50°f or higher than 110°f, neither in rainy days nor with a rainfall threat. Do not apply in humid surfaces. Do not apply when relative humidity is higher than 85% as in days or hours with thin fog, breeze, mist, dew, etc.

Use soap and water for washing your skin. Clean tools with water after use them. This product is ready to use, do not add water.


KEEP OUT OF REACH OF CHILDREN.

Storage:

Store in a cool and dry place, the container must be tightly closed. Do not stow more than three buckets.

Update: June 30/2020. These technical specifications replace any previous one up to this date. Visit our webpage www.impacusa.com where you can find the current version. Subjected to changes without notice.











TEST	VALUE	STANDARD
Consistency	Semi-thick	
Density	10.85 – 11.68 lb/gal	ASTM D-1475
Viscosity	30,000 - 35,000 cps	ASTM D-2196
pН	9 - 10	ASTM E-70
Solids	63%	ASTM D-1644
Elongation	> 300%	ASTM D-2370
Coverage*	3 ft2 / 1 qt	
Presentation	1 gal / 5 gal	
Color	White	

*Depends on surface porosity and roughness. Based on two coats.



LEED:

Impac Premium Product:

SS-CREDIT 7 HEAT ISLAND EFFECT: ROOF SRI Value: 113 CRRC Listing: Yes Energy Star Listing: Yes

Update: June 30/2020. These technical specifications replace any previous one up to this date. Visit our webpage www.impacusa.com where you can find the current version. Subjected to changes without notice.